



Cart	Width	Height	Length (handle in)	Length (handle out)	Weight
Narrow	30 1/2"	40 1/8"	50 1/2"	60"	88 lbs
Wide	53 1/4"	40 1/8"	50 1/2"	60"	110 lbs

**Applications:**

The CT Cart narrow is designed to hold up to 6 round composite core tables from 42" to as large as 72" round. This cart is designed to fit through common doorways and into elevators.

The CT Cart wide holds the same size tables. However, it will hold up to 12 tables. This cart is 53 1/4" wide and, will not fit through a common door. You will need a double door system with at least a 55" opening.

**Primary Structure:**

The cart shall consist of a steel frame, and is designed to roll easily on 6" rounded tread wheels with roller bearings. A handle is provided at the rear of the cart. The handle adjusts to accommodate tables from 42" to 72". The loading ramp is covered with neoprene rubber to guard against table edge wear.

**Casters:**

The wheels shall be 2" wide x 6" diameter, rounded, soft, thermoplastic elastomer, with straight roller bearings. The back wheels shall be contained in a swivel caster rig with brake. The casters and wheels shall have a dynamic load capacity of not less than 450 pounds each.

Part	Material Size
Main Rails	3"x 2" x 3/16" angle iron
Ramps Front & Rear	14 gauge (.083) sheet metal
Caster Plate	4" x 3/8" flat strap (.375)
Handle Material	1 1/4" x 14 gauge (.083) round tubing
Wheel Guards	3" x 3/16" (.188) flat strap

