



Durable Lightweight Tables & Chairs

SwiftSet® Folding Chair

SPECIFICATIONS

Seat Height	Overall Height	Width	Weight	Seat Depth	Footprint
18.5" (47cm) banquet	34.5" (88cm)	18" (46cm)	11.5 lbs. (5.2kg)	15.75" (40cm)	21" L x 18" W (53 x 46cm)

Frame: Main support frame is made using 1.25"x .625" [3.2cm x 1.6cm] x 18 gauge oval steel tubing. Cross bars consist of identical oval tubing firmly welded to each leg. Chair will support more than 1000 lbs.

Seat & Back: Seat and back portions are injection molded using toughened, UV stabilized, polypropylene. Plastic is molded in a variety of colors. Seat and back are attached to corresponding frame members using .47" [12mm] diameter steel blind rivets.

Upholstery: Optional upholstery is attached to 1/8" thick injection molded polypropylene seat and back using upholstery staples. These upholstery assemblies slide and lock into injection molded polypropylene seat pan and seat back housings. The housing assemblies are attached to the base and steel tube using .47" [12mm] diameter blind steel rivets.

Padding: Optional seat foam is 1.5", back foam is .75". Density is 2.5 or 1.6.

Standards: All upholstery and foam meet or exceeds California Bulletin 117 and is CFC Free. Optional NFPA 260A Class 1 Foam is available upon request or Kevlar upholstery lining is available if California TB 133 compliance is required. Meets or exceeds ANSI BIFMA testing as determined by an independent lab.


Frame Finish: Steel Finish is electrostatically applied, heat-cured powder paint formulated for indoor and outdoor use.

Feet: Feet are injection molded using a non-marring thermo-

plastic elastomer. Combined foot to floor contact is not less than 3.8 square inches [9.6 square centimeters].

Seat Support: Seat support frame is constructed of .120"x .75" [3mm x19mm] steel bar.

Crossbar Cover: Optional snap on cover measures 14.5" x 1.25" [37cm x 3.2cm] and is made of exterior grade RPVC. Cover protects from scuffs and scratches.



Crossbar Cover

Folding: Folding mechanism is a 4-bar type linkage that is flat when folded and a rigid triangle shape when unfolded. Mechanism is joined by solid steel .25" [.63cm] diameter rivets.

Stacking: The shape and construction of the chair provides stable, positive indexing when stacked. Stacking density is 4.75" [12cm] for the first chair, each additional chair is 1.5" [4cm]. Maximum stack height is 45 units.

Warranty: SwiftSet® Folding chairs are warranted to be free from defects in materials and workmanship under normal use, service, and handling for twelve (12) years from the date of purchase.

Note: Some product features are optional. Please contact your sales rep or refer to your Order Acknowledgement or Customer Order form for details.

