



Durable Lightweight Tables & Chairs

Mity-Lite Mobile Staging™

Specifications

Size	Length	Width	Storage Dimensions (legs folded)	Height	Weight	Shipping Dimensions
4' x 8' stage	96" (244cm)	48" (122cm)	20" x 54.5" (51cm x 138cm)	16"-24" (41-61cm)	277 lbs (126kg)	49" x 21" x 60" (125cm x 53cm x 152cm)
4' x 8' stage	96" (244cm)	48" (122cm)	20" x 62.5" (51cm x 159cm)	24"-32" (61-81cm)	281 lbs (127kg)	49" x 21" x 68" (125cm x 53cm x 172cm)

Deck: Constructed of a steel tube frame and a 5/8" exterior-grade, solid core fir plywood with 6005 aluminum alloy edge protection. The edge protection is no wider than 1/8" wide around the perimeter of each deck. All steel tube in the chassis meets ASTM A513 specifications and all steel components are finished with a black powder coat finish. Nylon bushings are also utilized to protect against cracks forming between the decks due to uneven surfaces. Casters are made of non-marring polyurethane tread locked to a polyolefin core and rated for 300-pound load. All threaded hardware is zinc plated.


Surface: Black low-maintenance poly-tread (slip-resistant polypropylene.)

Folding Mechanism: A counterbalance is used in the folding mechanism requiring minimal lift to open and close the stage. In transportation mode – the product has a low center of gravity, allowing the operator to see over the deck during transport. The deck also automatically locks into position to avoid an unexpected opening while moving to and from storage.

Positive Lock: The deck automatically locks in position in both the transportation and performance modes.


Ganging: Each frame has two 17" long nylon straps to connect to adjoining decks. The straps are made of 2" nylon webbing and are fastened with a hook-and-loop Velcro™.

Stairs (optional): Casters are strategically placed on one side of stairs for easy transportation but are not used while in performance mode. The stair tread is 12" deep and 36" wide and is coated with a black, non-skid polymeric resin. No tools required for set up or takedown.



Stairs

Guardrails (optional): Made of tubular steel measuring 42" in height and has a lower bar that serves as a chair stop. The Guardrail is attached by using grippers that pinch onto the top and bottom of the deck. No tools required for set up or takedown.



Guardrails

Warranty: Mity-Lite Mobile Staging™ is warranted to be free from manufacturer defects in materials and workmanship under normal use, service, and handling for a period of three (3) years from the date of purchase.

